

02-JUN-2004 16:41 FROM ORBOTECH

TO 0017038729306

P.01/04



Office of Legal Advisor

Orbotech Ltd.  
P.O. Box 215  
Yavne 81102, Israel

Unofficial

Tel: 972-8-942-3614

Fax: 972-8-942-3626

RECEIVED  
CENTRAL FAX CENTER

## TELEFAX MESSAGE

JUN 02 2004

DESTINATION :	<u>VSPTO</u>	Date :	<u>02/06/2004</u>
Attention :	<u>Ex Michael Nahrin</u>	Fax. No. :	<u>(203) 872-9306</u>
	<u>Ex John Barlow</u>	Msg. No. :	
Copies to :		Total pages :	<u>4</u>
From :	<u>Michael Faibisch, Adv.</u>	(including cover page)	
Subject :	<u>VSSN: 09/735,872</u>		

This Transmission Contains Attorney Client Privileged Information

If you are not the intended recipient or if you have any difficulties receiving this transmission, please call 972-8-942-3609

Document3

RECEIVED  
CENTRAL FAX CENTER

JUN 02 2004

MEMORANDUM  
NOT TO BE ENTERED

Unofficial

Application: 09/735,872  
Pulse Light Pattern WriterSTC Ref: 51811  
Orbotech Ref: 524Attention: Examiner Michael Nghiem  
Examiner John Barlow

Fax: (703) 872-9306

The following is being provided in advance of an interview to be held with Applicant's representative, Sanford T. Colb.

Regarding claim 61: Rejection not applicable because prior reference and application commonly owned.

## Proposed Claim amendments:

1. (currently amended) Apparatus for transmitting information at a data rate comprising:

a pulsed light source that produces pulsed light;

a data signal source that provides data signals; and

a modulator that receives the pulsed light and the data signals and selectively modulates the pulsed light with a modulating signal responsive to the data signals and a modulator that asynchronously modulates the pulsed light at a data rate that is higher than a pulse repetition rate of a modulated the pulsed light.

5. (currently amended) Apparatus for recording an image on a photosensitive surface, comprising:

a pulsed light source that produces pulsed light;

a data signal source that provides data signals;

a modulator that receives the pulsed light and the data signals and selectively modulates the pulsed light with a modulating signal responsive to the data signals ~~a modulator that modulates the pulsed light at a data rate that is higher than a pulse repetition rate of a modulated the pulsed light; and~~

a scanner that scans the modulated pulsed light over the surface.

26. (currently amended) A method for transmitting information at a data rate comprising:

providing pulsed light that is pulsed; and

providing data signals;

selectively modulating the pulsed light with a modulating signal responsive to the data signals

~~asynchronously modulating the pulsed light at a data rate that is higher than a pulse repetition rate of a modulated the pulsed light.~~

29. (currently amended) A method for recording an image on a photosensitive surface, comprising:

providing pulsed light that is pulsed;

providing data signals;

selectively modulating the pulsed light with a modulating signal responsive to the data signals ~~modulating the pulsed light at a data rate that is higher than a pulse repetition rate of a modulated the pulsed light; and~~

scanning the modulated pulsed light over the surface to record an image.

49. (ALLOWED) Apparatus for exposing a pattern on a photosensitive surface comprising:

a laser light source providing a beam formed of successive substantially instantaneous laser pulses separated by a time interval;

a data signal source that provides data signals;

a modulator that receives the beam and the data signals and selectively modulates the beam with a modulating signal responsive to the data signals for a time period longer than said time interval, such that the modulating signal is operative to modulate at least two successive pulses; and

an optical subsystem that receives the modulated beam and projects an image of the modulator onto a photosensitive surface to expose a pattern thereon according to said modulating signal, wherein the modulating signal is an acoustic wave and wherein an attribute of the modulating signal changes between at least some of the two successive pulses.

61. Apparatus for recording an image on a photosensitive surface, comprising:  
a pulsed light source that produces pulsed light having a first wavelength and a pulsed repetition rate;

a wavelength converter external to the pulsed light source that receives said pulsed light and outputs wavelength converted pulsed light having a second wavelength which is less than the first wavelength;

a modulator that receives and modulates the wavelength converted pulsed light; and

a scanner that scans the modulated wavelength converted pulsed light over the surface.